



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : E04H 1/00, E04C 2/28 B21C 37/02, B23P 17/00	A1	(11) International Publication Number: WO 94/11597 (43) International Publication Date: 26 May 1994 (26.05.94)
---	----	--

(21) International Application Number: PCT/US93/10842
(22) International Filing Date: 10 November 1993 (10.11.93)
(30) Priority data:
07/974,627 12 November 1992 (12.11.92) US

(71)(72) Applicant and Inventor: JOHNSON, David, L. [US/
US]; 83 Windbeam Avenue, Ringwood, NJ 07456 (US).

(74) Agents: CONLIN, David, G. et al.; Dike, Bronstein, Ro-
berts & Cushman, 130 Water Street, Boston, MA 02109
(US).


(81) Designated States: CA, JP, European patent (AT, BE, CH,
DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT,
SE).

Published
With international search report.

(54) Title: METALLIC WALL FRAMING, METHOD AND APPARATUS FOR PRODUCING SAME

(57) Abstract

Metallic track members (10) having locking slots (32) designed for receiving and retaining metallic stud members (22) that contain construction aids (64 and 66) enable the assembly of metallic frames used in the construction of buildings. A flat metallic strip is converted to a W-shaped metallic track member (10) by a series of stamping, bending and severing steps. U-shaped stud members (22), manufactured in a similar manner are inserted into the track members (10) and held relatively stable by upper and lower track members (10 and 37). An upper track member (37) can be the same shaped design as the lower member or can be U-shaped with stud retaining means into which the stud members (22) can slip-fit. The process for manufacturing is adaptable for computer aided manufacturing using data from the computer aid design of the building. Manufacturing equipment for the manufacture of the construction members is relatively light-weight and can be transported to the job site.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	MR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LJ	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

METALLIC WALL FRAMING, METHOD AND APPARATUS FOR PRODUCING SAME

This invention relates to metallic wall framing for use in residential and commercial buildings. More particularly, it relates to metal framing that comprises upper and lower metallic track members and metallic vertical members connecting the upper and lower track members, the individual members, a method for producing the individual members from flat metallic stock and a portable apparatus for producing the members from flat metallic stock.

BACKGROUND OF THE INVENTION

10 Framing used in residential and commercial buildings generally have upper and lower horizontal members which are generally spaced apart vertically by a distance that corresponds to the vertical wall height. The upper and lower members which are referred to as "plates", or "runners" or "tracks", particularly when materials other than wood are used. In this application, the term "track member" is used and refers to the horizontal members. The vertical members of the framing that connect the upper and lower tracks are referred to as "studs" or "risers". In the context of the present invention the vertical members for connecting the upper and lower tracks members are referred to as a "stud members".

20

In commercial or residential buildings in which fire proofing or fire resistance is desired, conventional wood framing can not be used. As a result, there have been numerous metallic framing designs proposed, such as those disclosed in United States Patents No. 2,173,721; 2,966,708;

-2-

3,001,615; 3,536,345; 3,680,271; 4,805,364; 4,854,096 and
4,918,899. However, there remains a need for a metallic track members
which are capable of easily receiving and securely retaining studs and
which track can be fabricated from flat metallic sheet at the job site and
5 which can be assembled into construction framing with a minimum of
labor and material costs. Prior metallic construction members such as
those illustrated in the above patents lacked one or more of the above
qualities. Certain members could not be readily manufactured at the job
site. In certain types of members the stud member tended to move in
10 one or more directions. Other designs of metallic construction members
resulted in excessive field assembly time. Still other types of designs
were cumbersome to transport from the production facility at which they
were fabricated to the job site where they were to be used.

15 It is believed, therefore, that metallic members which obviates
many of the disadvantages of prior metallic framing members would be an
advancement in the art.

SUMMARY OF THE INVENTION

20 In accordance with one aspect of this invention there is
provided a metallic longitudinal track that comprises first and second
substantially identical and parallel vertical wall sections forming opposing
vertical walls of the track, first and second substantially identical
horizontal base sections of the track having a first width and projecting at
25 about 90° from the corresponding adjacent wall sections at one extremity
along the entire length thereof, first and second substantially identical
vertical intermediate sections and projecting angularly from an extremity
of adjacent base sections opposite to the respective wall sections and

-3-

having transverse cross-sections in the shape of the sides and top of a truncated isosceles triangle; the intermediate sections have a plurality of transversely aligned locking slots for receiving and retaining portions of vertical transverse metallic stud members and a third horizontal base
5 section having a second width between the vertical intermediate sections.

In accordance with another aspect of this invention there is provided a metallic stud member having a predetermined length comprising first and second spaced apart parallel wall sections extending
10 the length of the stud member, a transition section perpendicular to and connecting the wall sections at one extremity of each wall section and flange sections projecting perpendicular from the opposing extremity of each corresponding wall section. The transition section has at least one construction aids at predetermined locations selected from the group
15 consisting of:

- i) a first receiving means capable of receiving and securing a metallic transverse member interconnecting an adjacent transition section of an adjacent stud member,
- ii) a second receiving means capable of receiving and securing a
20 mounting member for an electrical box,
- iii) a passageway for enabling an electrical conduit to traverse said stud member,
- iv) a pair of slots for receiving and securing end tabs of transverse framing for a door or a window and
25 v) an opening at the lower extremity of the transition section for passage of utility conduits.

In still other embodiments of this invention there are provided methods of producing the metallic track and stud members from a relatively flat metallic sheet. Additional embodiments provide portable mechanisms for producing the metallic track and stud members at the job site. Still other embodiments provide framing that comprises a pair of vertically spaced apart track members as set forth above and a plurality of U-shaped metallic stud members having the construction aids as described above and construction aids for mounting internal walls.

10 **BRIEF DESCRIPTION OF THE DRAWINGS**

Fig. 1 is a fragmentary perspective view showing a lower track member interconnected with a vertical U-shaped stud member.

Fig. 2 is an end view of a track member.

15

Fig. 3 is a top view of the profile of a typical locking slot utilized in the practice of this invention.

Fig. 4 is a broken-away fragmentary perspective view showing an optional upper track member connected to the upper end of a slide member of this invention.

20

Fig. 5 is an end view optional upper track member.

Fig. 6 is a view of a segment of the optional upper track showing stud retainer of the optional upper track.

25

Fig. 7 is a perspective view illustration framing utilizing upper and lower track members of the present invention and stud members of the present invention.

5 Fig. 8 is fragmentary perspective view of the tabs of a head stock for door or window framing.

Fig. 9 is a detail view of a typical opening for receiving an angle member which will connect adjacent stud members in an interlocking
10 relationship.

Fig. 10 is a fragmentary side view of a stud member of this invention is made and in which typical construction aids have been stamped.
15

Fig. 11 is a side view showing the initial insertion of retaining clips of an electrical conduit box into the receiving slot of the stud.

Fig. 12 is a side view showing an electrical conduit box mounted to
20 a stud member.

Fig. 13 is a plan view showing a self locking furring channel mounting strip construction aid.

25 Fig. 14 is a side view showing the self locking furring channel mounting strip construction aid.

Fig. 15 is a fragmentary top view of a flat metallic plate from which a track member of this invention is made in which typical locking slots have been stamped.

5 Fig. 16 is a cross-sectional view of a stud member taken along line A-A in Fig. 10.

Fig. 17 is a detail view of a typical access opening at the lower end of the stud through which various utility conduits can pass.

10

Fig. 18 is a detail view of showing typical openings for clips to retain an electrical outlet boxes.

Fig. 19 is a detail view of a conduit passageway for electrical
15 conduit.

Fig. 20 is a detail view of slots for receiving end tabs of header stock for window and door framing.

20 Fig. 21 is a flow diagram illustrating the method of producing the track members of this invention.

Fig. 22 is a flow diagram illustrating the computer aided manufacturing method and apparatus of this invention.

25

DESCRIPTION OF THE PREFERRED EMBODIMENTS

For a better understanding of the present invention together with other and further objects, advantages and capabilities thereof, reference is

-7-

made to the following detailed description and appended claims in connection with the above summary of the invention and the brief description of the drawings.

5 The track and stud members are preferably made from galvanized steel. However, any fire resistant metal sheet can be used which can be formed into the required shape without the creation of undue stress in the member. A typical preferred material is a sheet of 16 gage galvanized steel. In many instances the track members will be produced in a
10 standard length, such as 12 feet, and transported to the job site, however, as hereafter described, portable on-site production equipment can be used to fabricate the track members from a roll of galvanized steel. The portable production facility is particularly useful when the amount of framing exceeds about 20,000 linear feet.

15 A typical roll of suitable metallic sheet from which the track members are fabricated will have a preferred width of about 12 inches. In a similar fashion, the stud members can also be formed from a flat sheet having a typical width of about 7 inches.

20 With particular reference to Figs. 1 and 2, a lower track member 10 has a first wall section 12, and a second substantially identical and parallel vertical wall section 14 that form opposing vertical walls of the track. A first horizontal base section 16 and a second horizontal base
25 section 18 receives flange sections 20, 21 of the stud member 22. The first base section 16 and the second base section 18 are fabricated sufficiently narrow to prevent the stud member 22 from moving appreciably in the transverse direction. The base sections, 16, 18 project

at about 90° from corresponding adjacent wall sections 12, 16 at the extremities A, J. A first vertical intermediate member 24 projects from extremity B of adjacent base section 16. A second vertical intermediate member 26 which is substantially identical to first vertical intermediate member 24 projects from the corresponding extremity I of the second base section 18. Both intermediate members have a transverse cross-sections in the shape of the sides 27a, 27b, 27c, 27d and tops 28a, 28b of truncated isosceles triangles. A third horizontal base section 29 extends between the vertical intermediate members 24 and 26. Thus, as is portrayed in Fig. 2 the track member 10 is a W-shaped member. The first intermediate member has a locking slot 30 as shown in detail in Fig. 3. The second intermediate member 26 has a similar locking slot 32. The locking slots 30, 32 receive and retain portions 34, 36 of the transverse stud member 22. A series of serrations extending from locking slot 30 form a series of locking teeth; 38 a-d, 39 a-d, 40 a-d and 41 a-d, which enable a lower portion 34 of stud member 22 to be inserted and retained in locking slot 30. In similar fashion another lower portion 36 of stud member 22 is retained in locking slot 32. An upper track member 37, Fig. 7 has a configuration similar to the lower track member 10 and receives and retains corresponding upper extremities of the stud member 22 similar to the lower track member 10. The combination of the upper and lower track members having locking slots similar to those shown as 30, 32 in Fig. 1 and 3 and the first and second base members similar to those shown as 16, 18 in Fig. 2 prevent the stud members from moving vertically, horizontally or longitudinally. Additionally, the upper and lower track members and the stud members can be assembled and moved into a desired position thereby reducing the time required for constructing wall framing of a building.

With particular reference to the fragmental views of Fig. 4 and top view Fig. 16, the U-shaped stud member has parallel wall sections 38, 40 with a transition section 42 connecting wall sections 38, 40. As is shown in Fig. 4 the stud member is inserted into an alternate upper track 44. With particular reference to Fig. 5 and 6, the alternate upper track 44 has vertical walls 45, 46 and upper track transition section 47 between the walls 45, 46. Stud retaining means 48a, 48b project from wall 45. In a similar manner stud retaining means 49a, 49b project from wall 46 and are aligned with the stud retaining means 48a, 48b of wall 45 thereby enabling the wall sections 38, 40 of stud member 22 to be inserted between the stud retaining means 48a, 48b, 49a and 49b.

With particular reference to Fig. 7 there is shown a wall framing segment 50 utilizing the concepts of this invention. Lower track member 20 receives and retains a plurality of stud members 22a through 22e. An upper track member 37, substantially identical to lower track member 10, receives stud members 22a through 22e. Angle reinforcing members 52a and 52b interlock stud members 22a, 22b and 22c. Similarly, angle reinforcing members 52c and 52d interlock stud members 22c and 22d, a door framing member 54 interconnects stud members 52c and 52d.

Fig. 8 is an end segment of door framing member 54 in which tabs 56a and 56b are inserted into slots 58a and 58b of stud 22c. The slots in the stud are described with reference to Fig. 20 herein. Similar tabs fit into slots in stud 22d and the opposing end of door framing member 54.

With particular reference to Fig. 9 there is shown an opening 60 in stud member 22 which receives and retains angle reinforcing member 54.

-10-

With particular reference to Fig. 10, there is shown a fragmentary side view of a stud member 22. On access openings 62a and 62b which are described in detail in Fig. 17 are a substantially centered in the transition section 42, conduit box receiving stations 64, 66, which are described in detail with reference to Fig. 18 are vertically aligned and are at about 18 inches and 48 inches respectively from the lower end 68 of stud 22. Conduit passageways 70, 72 are detailed with respect to Fig. 19. Opening 60 which was described in detail with respect to Fig. 9 and framing slots 58a, 58b.

10

With particular reference to Fig. 11 the upper conduit box tab 74 2s inserted into upper slot 75 of the conduit box receiving station. After the initial insertion as shown in Fig. 11, the box is rotated so that lower conduit box tab 76 can be inserted in lower slot 77 as shown in Fig. 12. After insertion of the lower conduit box tab 76, the conduit box 78 is lowered and the box 78 is mounted on side of stud 22.

15

With particular reference to Figs. 13 and 14 there is shown a construction aid that can be used in conjunction with internal wall construction. While the construction aid is shown with respect to mounting upon a masonry or concrete wall which often are not true so that if an internal wall is mounted in a conventional manner the wall will not be true or level with respect to the other wall, the ceiling or the floor of the room. Construction aid comprises strip 80 having projections 82, 84 that provide for receiving and retaining transverse member 86 having a relatively flat surface. Strip 80 is anchored to the underlying wall by anchoring means 87, 88. Shims, not shown, can be used at the anchoring means to provide a surface of member 86 that will enable the

20

25

-11-

internal wall mounted thereupon to be true, thereby enabling the internal wall to be in the proper geometric relationship.

With particular reference to Fig. 15, there is shown a fragmentary
5 plan view of a metallic plate 88, such as 16 gage galvanized steel, in
which a series of locking slots 30 a-k and 32 a-k are cut the slots are
described in detail above with particular reference Fig. 3. A spacing " d_1 "
is shown. The spacings are chosen to enable the studs to have the
appropriate spacing to provide construction flexibility. A spacing of 2
10 inches is preferred. The plate 88, after the locking slots have been cut, is
heated to a metal deforming temperature and in a series of passes the
plate is bent at dotted lines A-A through J-J to form a track having an end
view as shown in Fig. 2. The metal deformation produces a track having
wall sections 12, 14, first and second base sections 16, 18 and
15 intermediate sections 24, 26, and a third base section 28.

With particular reference to Fig. 16, a cross section taken along line
A-A of Fig. 10 the U-shaped metallic stud member 22 has first and
second spaced apart parallel wall sections 38, 40 extending the length of
20 the member, a transition section 42 is perpendicular to and connecting
the wall sections 38, 40 at the extremities 43a, 43b of each wall section
38, 40. Flange sections 20, 21 project perpendicular from corresponding
wall sections 38, 40. As shown in Fig. 10, the transition section 42 has
various construction aids at predetermined locations along the length
25 thereof.

With particular reference to Fig. 17, there is shown a detail view of
typical access openings 62. The openings are at the lower and upper

-12-

ends respectively of the transition section 42 of stud member 22. The openings as shown in Fig. 10 as 62a, 62b enable the various utility conduits such as water pipes and the like to pass through stud member 22.

5

With particular reference to Fig. 18, conduit box receiver station 64, comprises vertically aligned conduit box tab receiving means 88a, 89a which also contain upper and lower slots 75, 77 for receiving tabs from a conduit box 78 as shown in Figs. 11 and 12. Another pair of
10 identical means 88b and 89b are located at the opposite side of the transition section 64 of the stud member 22 so that electrical conduit boxes can be mounted for access to either side of the wall that is formed on either side of the framing.

15

With particular reference to Fig. 19 opening 72 in stud 22 is of a sufficient size to enable electrical conduit to be passed through the stud member 22.

20

With particular reference to Fig. 20 slots 58a and 58b are sized to receive and retain tab 56a and 56b of the wall opening framing 54, shown as a door 53 in Fig. 7. If desired, however, similar framing can be used to provide opening for windows.

25

Fig. 21 illustrates the process of forming the metallic track members of this invention. A sheet of metallic material such as galvanized steel, cold rolled steel, aluminum, or other metals and metal alloys can be used. The flat metallic sheet material, typically 12 inches in width can be used from a spool or reel. The flat sheet, after being

-13-

unwound from the spool or reel is stamped at step 92 to produce locking slots as shown in Fig. 3 thereby producing a strip of material as shown in Fig. 15. A first series of indicants are placed at intervals of 24 inches starting at one end of the stamped sheet. A second series of indicants
5 are placed at intervals of 12 inches starting at 12 inches from the same end of the stamped sheet. A third set of indicants are placed at intervals of 16 inches starting at 16 inches from the same end of the stamped sheet. A simple method of providing indicants is to use paint wheels that mark a distinctive line or mark for each series of indicants. For example,
10 a 1/4" black line can be used for the first series of indicants, 3/16" red lines for the second series of indicants and 1/8" yellow lines for the third series of indicants are suitable.

With particular reference to Fig. 22 the construction design input of
15 the particular building to be built is programmed, either downloaded from the CAD system used to design the building or programmed manually and fed into the computer processing station 101 which yields a series of outputs.

20 The data relating to the pressure required to stamp a particular metal sheet being processed, which will be dependent upon the thickness of the metal and the material of construction, can be processed and fed to the pressure controller 103. The pressure controller 103 can regulate the stamping station 92 and as explained previously, indicants at
25 preselected locations are useful to assist in the construction. The data for the linear repetitive location of the series of indicants can be processed and fed to location controller 104 which will operate the marking device 94 which will locate the first, second and third sets of indicants on the

-14-

sheet. The configuration of the track, whether of the type shown in Fig. 2 or the type shown in Fig. 5 is programmed and inputted into the computer processing station 101. The output from the computer processing station provided shape controller 105 which signals the

5 bending wheel station, used to shape the flat sheet into the desired configuration. The input from the design of the building is used to program the length of each segment of track member that is required. The computer station 101 feeds the data to the locating control 106 which provides the desired signals to the severing station 98 that

10 provides a shearing action to cut the processed track member to the lengths required in the building design. Additionally, the input from the building design can be used to provide outputs from the computer processing station to provide the locations of the locking slots. Thus, the location of the studs at the standard spacing can be designed as well as

15 the location and width of wall openings such as doors, windows, floor to ceiling openings can also be fed into the manufacturing design of the track members.

A metallic sheet holding means such as a spool or reel holds the

20 metallic strip prior to the sheet being fed to metal stamper 92 wherein a series of locking slots as shown in Fig. 15 as 30 a-k and 32 a-k are stamped at intervals d_1 , as shown on Fig. 15. The distance d_1 is 2 inches as an example, however, d_1 can be varied as desired to give design flexibility. For example, in countries in which the metric system is used

25 the distance d_1 can be varied from about 50 cm to about 100 cm to give a suitable design variability. The metal strip 108 is thereafter fed to a marking device 111 containing three retractable paint wheels 112, 113 and 114. As described with reference to Fig. 21, the paint wheels are

-15-

lowered at a prescribed location to provide three separate series of indicants. Each indicant is spaced equal distance from an adjacent indicant of the same type as was described with reference to Fig. 21. After indicants have been marked on metal strip by paint wheels the strip

5 is fed to a seaming press that provides seams prior to bending. The flat strip enters a series of bending wheels which in a series of 10 bends changes the profile to a track 10 as shown in profile in Fig. 2. The track is sheared at a predetermined length. The shearing to produce the desired length can be after the bending thus enabling the metal strip to be in

10 tension to convey the material through the various work stations. After the work is performed the formed track can be cut to the desired length l_1 , such as 12 feet. If desired the flat strip can be cut to length l_1 at any location prior to the last forming location. The metal forming production unit can be either self-propelled or can be transported to the job site by

15 an external means such as a tractor.

While there have been shown what are considered to be the preferred embodiments of the invention, other and further modification may occur to those skilled in the art to which the invention pertains.

20

WHAT IS CLAIMED IS:

1. A metallic longitudinal track member comprising
 - a) first and second substantially identical and parallel vertical
5 wall sections forming opposing vertical walls of the track,
 - b) first and second substantially identical horizontal base
sections having a first width and projecting at about 90° from
corresponding adjacent wall sections at one extremity and along the entire
length thereof,
10 c) first and second substantially identical vertical intermediate
sections extending the length of the track and projecting from an
extremity of adjacent base sections opposite to the respective wall
sections and having transverse cross-sections in the shape of the sides
and the tops of truncated isosceles triangles, each intermediate section
15 having at least one locking slot adapted for receiving and retaining
portions of a metallic stud member and
 - d) a third horizontal base section having a second width
between the vertical intermediate sections.- 20 2. A metallic track according to claim 1 wherein the locking
slots in the first and second intermediate members are aligned in a
transverse direction normal to the longitudinal axis of the track.
- 3. A metallic track according to claim 2 wherein the locking
25 slots comprise a plurality of locking teeth in the sides of each vertical
intermediate section.

-17-

4. A metallic track according to claim 3 wherein each intermediate section contains a plurality of the locking slots at predetermined locations along the length of the track.
- 5 5. A metallic track according to claim 4 wherein adjacent aligned locking slots have an equal distance therebetween.
6. A metallic track according to claim 1 having a distance between the first and second vertical wall sections of from about 3.5 to
10 about 4.0 inches.
7. A metallic track according to claim 1 wherein the metal is galvanized steel.
- 15 8. A metallic stud member comprising
- a) first and second spaced apart parallel wall sections extending the length of the stud member,
- b) a transition section connecting the wall sections at one edge of each wall section and containing at least one construction aid,
- 20 c) a first flange section extending the length of the first wall section and projecting perpendicular from the other edge of the first wall section and
- d) a second flange section extending the length of the second wall section and projecting perpendicular from the other edge of the
25 second wall section.
9. A metallic stud member according to claim 8 wherein the construction aid is a first receiving means capable of receiving and

-18-

securing a metallic transverse member interconnecting an adjacent transition section of an adjacent stud member.

10. A metallic stud member according to claim 8 wherein the construction aid is at least a first pair of vertically aligned slots for receiving and securing mounting tabs of an electrical conduit box at a first distance from a first end of the stud member.

11. A metallic stud member according to claim 10 wherein the first pair of vertically aligned slots is along one edge of the transition section and a second pair of vertically aligned slots at the opposing edge of the transition section at the first distance from the first end of the stud member.

12. A metallic stud member according to claim 11 having third and fourth pairs of vertically aligned slots substantially identical to the first and second pairs of vertically aligned slots at a second distance from the first end of the stud member.

13. A metallic stud member according to claim 12 wherein the first distance is about 18 inches and the second distance is about 48 inches.

14. A metallic stud member according to claim 8 wherein the construction aid is a passageway for enabling an electrical conduit to traverse said stud member.

-19-

15. A metallic stud member according to claim 8 wherein the construction aid is a pair of slots for receiving and securing end tabs of transverse framing for a wall opening.

5 16. A metallic stud member according to claim 8 wherein the construction aid is an opening at an extremity of the transition section for passage of utility conduits.

10 17. A metallic frame comprising
a) a lower track member having a longitudinal axis and comprising
i) first and second substantially identical and parallel vertical wall sections forming opposing vertical walls of the track,
ii) first and second substantially identical horizontal base
15 sections having a first width and projecting at about 90° from corresponding adjacent wall sections at one extremity and along the entire length thereof,
iii) first and second substantially identical vertical intermediate sections extending the length of the track and projecting
20 from an extremity of adjacent base sections opposite to the respective wall sections and having transverse cross-sections in the shape of the sides and the tops of a truncated isosceles triangles, each intermediate section having at least one locking slot, the locking slots being in alignment in a direction transverse and normal to the longitudinal axis of
25 the track member and
iv) a third horizontal base section having a second width between the vertical intermediate sections,

-20-

b) a plurality of vertical stud members transverse to the horizontal axis of the track member and having portions at one end thereof inserted into the locking slot of the lower track member, each stud member comprising,

- 5 i) first and second spaced apart parallel wall sections extending the height of the stud member,
- ii) a transition section connecting the wall sections at one edge of each wall section and containing at least one construction aid,
- iii) a first flange section extending along the first wall
- 10 section and at about 90° from the other edge of the first wall section and
- iv) a second flange section extending the length of the second wall section and projecting perpendicular from the other edge of the second wall section
- one end of each of the first and second flange sections
- 15 contacting the first and second base sections of the track member and
- c) an upper track member adapted for receiving and retaining an opposing end of the stud members in a relatively fixed position.

20 18. A metal frame according to claim 17 wherein the upper track member has the same configuration as the lower track member.

 19. A metal frame according to claim 17 wherein the upper track member comprises

- 25 a) a first and second parallel walls extending the length of the upper track member,
- b) a transition section connecting the walls at one edge of each wall,
- c) a plurality of stud retaining means on the first wall and

-21-

d) a plurality of stud retaining means on the second wall.

20. A metal frame according to claim 19 wherein the stud retaining means comprise a pair of projections spaced apart by a distance
5 corresponding to the width of the walls of the stud.

21. A metal frame according to claim 18 wherein the stud members have a first pair of vertically aligned slots for receiving and securing mounting tabs of an electrical conduit box at a first distance
10 from a first end of the stud member, a second pair of vertically aligned slots at the opposing edge of the transition section about 18 inches from the end of the stud member contacting the lower track member, third and fourth pairs of vertically aligned slots substantially identical to the first and second pairs of vertically aligned slots at about 48 inches from the
15 end of the stud member contacting the lower track member.

22. A metal frame according to claim 17 having a plurality of angle reinforcing members interlocking adjacent stud members.

20 23. A metal frame according to claim 17 having a wall opening framing member attached to and connecting at least two adjacent stud members wherein the adjacent stud members and the wall opening frame provide framing for an opening in a wall constructed utilizing the metal frame.

25

24. A metal frame according to claim 17 wherein the stud members have at least one construction aid selected from the group consisting of

-22-

- a) means for receiving and securing a metallic transverse member interconnecting an adjacent transition section of an adjacent stud member,
- b) means for receiving and securing a mounting member for an electrical box,
- c) passageway for an electrical conduit,
- d) means for receiving and securing transverse wall opening framing and
- e) an opening abutting a track member at an end of the transition section.

25. A process for producing a metallic track member comprising
- a) providing stud locking slots at selected locations in a relatively flat sheet of metallic material,
- b) marking the resulting slotted sheet at repetitive locations to provide indicants thereon,
- c) bending the slotted sheet containing the indicants to form a W-shaped track and
- d) severing the W-shaped track at a predetermined length.

26. A process according to claim 25 wherein step a), b) and d) are conducted sequentially.

27. A process according to claim 25 wherein the bending step comprises
- a) subjecting the sheet to a first bending moment along a first line parallel to the longitudinal axis of the sheet at a first distance from a first longitudinal edge of the sheet to form a bend and provide a first wall

-23-

section containing the first edge and an adjacent width of the sheet at about 90° angle from the first wall section,

b) subjecting the sheet to a second bending moment along a second line parallel to the first line at a second distance from the first line to form a second bend to provide a first base section and an adjacent width of the sheet at an acute angle away the first wall section,

c) subjecting the sheet to a third bending moment along a third line parallel to the longitudinal axis of the sheet at third distance from the second line to form a third bend to provide a first side of a first intermediate section and an adjacent width of the sheet parallel to the first base section,

d) subjecting the sheet to a fourth bending moment along a fourth line parallel to and at a fourth distance from the third line to form a fourth bend to provide a top to the first intermediate section, the top being above and parallel to the first base section and an adjacent width of the sheet at an acute angle away from the first wall section,

e) subjecting the sheet to a fifth bending moment along a fifth line that is parallel to the longitudinal axis of the sheet and at the third distance from the fourth line to form a fifth bend to provide a second side to a first intermediate section and an adjacent width of the sheet that is parallel and in the same plane as the first base section,

f) subjecting the sheet to a sixth bending moment along a sixth line parallel to the fifth line at the fourth distance from the fifth line to form a sixth bend to provide a second base section and an adjacent width of the sheet at an acute angle away the first wall section,

g) subjecting the sheet to a seventh bending moment along a seventh line parallel to the longitudinal axis of the sheet at the third distance from the sixth line to form a seventh bend to provide a first side

-24-

of a second intermediate section and an adjacent width of the sheet parallel to the second base section,

5 h) subjecting the sheet to an eighth bending moment along a eighth line parallel to and at the fourth distance from the seventh line to form a eighth bend to provide a top to the second intermediate section the top being above and parallel to the first base section and an adjacent width of the sheet at an acute angle away from the first wall section,

10 i) subjecting the sheet to a ninth bending moment along a ninth line that is parallel to the longitudinal axis of the sheet and at the third distance from the eighth line to form a ninth bend to provide a second side to a second intermediate section and an adjacent width of the sheet that is parallel and in the same plane as the first and second base sections and,

15 j) subjecting the sheet to a tenth bending moment along a tenth line parallel to the longitudinal axis of the sheet at the second distance from the ninth line to form a tenth bend to provide a third base section and at 90° therefrom a second wall section containing the opposite edge of the sheet at the first distance from the tenth line.

20 28. A process according to claim 27 wherein building design data is fed into a computer and steps a) through e) are controlled by computer generated signals.

25 29. A machine for manufacturing predetermined lengths of a shaped metallic track from a flat sheet of metal, the machine comprising

- a) a portable base having mounted thereon
- b) a metallic sheet holding means,

-25-

c) stamping means for cutting locking slots at preselected intervals along the length of the sheet,

d) a marking device for providing a series of indicants along the length of the sheet,

5 e) multiple bending stations for providing a series of bends in the metal sheet to form a W-shaped member and

f) means for severing the metallic material into predetermined lengths wherein the holding means, the stamping means and the bending station sequentially process the metal.

10

30. A machine according to claim 29 wherein the severing station is mounted downstream from the bending station.

15 31. A machine according to claim 30 wherein the marking device is downstream from the stamping means and upstream from the bending station.

32. A process for producing a metallic stud member of a predetermined length from a relatively flat metallic sheet comprising:

20 a) stamping at least one construction aid at a predetermined location in the flat sheet,

b) subjecting the flat sheet to bending steps to convert the flat sheet to a flanged U-shaped member and

25 d) severing at the predetermined length at a preselected time during the process.

33. A process according to claim 32 wherein the bending step comprises:

-26-

- 5 a) subjecting the sheet to a first bending movement along a first line parallel to the longitudinal axis of the sheet at a first distance from the edge of the sheet to form a bend and to provide a first flange section containing the first edge and an adjacent width of the sheet at about a 90° angle from the first flange section,
- 10 b) subjecting the sheet to a second bending movement along a second line parallel to the first line at a second distance from the first line to form a second bend and a first wall section at about 90° from the first flange and an adjacent width of the sheet at about 90° angle from the first wall,
- 15 c) subjecting the sheet to a third bending movement along a third line parallel to the second line at a third distance from the second line to form a third bend and a transition section containing the construction aid and an adjacent width of the sheet at about 90° from the transition section and
- 20 d) subjecting the sheet to a fourth bending movement along a fourth line parallel to the third at the second section distance from the third line to form a second wall section parallel to the first wall section and a second flange section having a width equal to the first distance.
- 25 34. A construction aid comprising a metallic strip comprising (a) a pair of projections for receiving and retaining a transverse member having a relative flat surface to which a flat wall surface can be mounted and (b) spaced apart enabling means for the metallic strip to be anchored to a surface on the side of the metallic strip opposite to the pair of projections.

1/8








FIG 3

2/8



3/8




FIG 7




FIG 9




FIG 8

4/8




FIG 10




FIG 11




FIG 12




FIG 13




FIG 14

5/8




FIG 15




FIG 18




FIG 16




FIG 17




FIG 19




FIG 20




FIG. 21

8/8




FIG. 22

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US93/10842

A. CLASSIFICATION OF SUBJECT MATTER IPC(5) :E04H 1/00; E04C 2/28; B21C 37/02; B23P 17/00 US CL :52/241, 656.1; 72/379.2; 29/897.31 According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) U.S. : 52/127.1, 238.1, 239, 240, 241, 274, 664, 656.1, 690; 72/180, 181, 379.2; 29/897.31, 897.312, 417, 33Q, 33S Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US, A, 4,448,004 (Thorsell) 15 May 1984, see entire document.	8, 9-16, 34
X	US, A, 4,236,473 (Behl) 02 December 1980, see entire document.	32, 33
A	US, A, 5,029,462 (Wakahara et al) 09 July 1991, see entire document.	1-34
A	US, A, 3,421,353 (Franc) 14 January 1969, see entire document.	1-34
A	US, A, 1,762,112 (White) 03 June 1930, see entire document.	29-31
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be part of particular relevance "E" earlier document published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "Z" document member of the same patent family	
Date of the actual completion of the international search 25 JANUARY 1994		Date of mailing of the international search report 09 FEB 1994
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231		Authorized officer <i>my Mean</i> JERRY REDMAN Telephone No. (703) 308-2168
Facsimile No. NOT APPLICABLE		